

LUNA BL



Integrated
Reflector with integrated LED unit

Durable
Impact-resistant polycarbonate casing (IK08)

CASING Polycarbonate, impact-resistant, IK08.

LAMP COVER Polycarbonate with integrated LED unit.

SEALS Age-resistant silicone seals.

ELECTRICAL COMPONENTS High power LED, LED converter.

ASSEMBLY Variable mounting distances with PRACHT-CLAMP-SYSTEM. Suitable for ceilings, wall, pendant and rail mounting.

FIELDS OF APPLICATION Parking garages, basements, workshops, 1:1 LL replacement.

Individual luminaire, colour temperature 4000 K, Ra>80, IP65

Power	Light distribution	Luminous flux	Item number	Length	Weight
1x22 W	120° wide	2800 lm	5211004	1200 mm	1.8 kg
1x43 W	120° wide	5400 lm	5211014	1200 mm	1.8 kg
1x31 W	120° wide	3800 lm	5211005	1500 mm	2.1 kg
1x52 W	120° wide	6500 lm	5211015	1500 mm	2.1 kg

ACCESSORIES

Through-wiring	Item number
3x1.5mm² SET LUNA BL 1.2m, consisting of rigid cable, Terminalblock one-sided	5552132
3x1.5mm² SET LUNA BL 1.5m, consisting of rigid cable, Terminalblock one-sided	5552135
5x2.5mm² SET LUNA BL 1.2m, consisting of rigid cable, 2x 5pol Terminalblock	5552152



Advanced
LIGHTING TECHNOLOGIES

Australia
New Zealand
Singapore

61 3 9800 5600
64 7 579 0163
65 6 844 2338

www.adlt.com.au
www.adlt.co.nz
www.adlt.com.sg

PRACHT®



Solid

High-quality
stainless steel clips

Easy Fix

Extremely fast assembly

ALL-ROUNDER

EXTREMELY FAST ASSEMBLY
DIFFUSER LUMINAIRE
HIGH QUALITY **ENECEC**
PRICE/PERFORMANCE
DUST-TIGHT
UNIFORM LIGHT
1:1 REPLACEMENT

3

YEAR
WARRANTY



50.000 h
OPERATIONAL LIFETIME



A++

IP65



-20°C ... +35°C