



**VARDAflex Eco CRI90 - 5 M-Rolle
Flex.LEDStrip, 24V, Innen, 3000K**
Article nr.: 82415

mit selbstklebender Rückseite, · für die Innenanwendung · · alle 100 mm / 7 LEDs teilbar · Anzahl der LEDs: 350 · LED Abstand: 14,28 mm · Ausstrahlwinkel: 120° · CRI: >90 · Lichtstrom pro Meter: 410 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 4,8 W · Lebensdauer L70B50: >= 36.000 h · Energieeffizienzklasse: G · LxBxH in mm: 5.000 x 8 x 2 · · Leichte lötfreie Montage durch Steckverbindungen (optional). · Maximale Länge pro Anschluss: 10 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle

TECHNICAL DATA

| | |
|-------------------------|--------------------|
| Unit Code | Stück |
| BAR code | 4012094824154 |
| Housing colour | Weiss |
| Length | 5000.00 mm |
| Width | 8.00 mm |
| Height | 2.00 mm |
| LED colour | ca. 3000K warmweiß |
| Lightoutput per fixture | 2050.00 lm |
| Lightoutput per LED | 5.85 lm |
| Lamp | Inklusive LED |





VARDAflex Eco CRI90 - 5 M-Rolle Flex.LEDStrip, 24V, Innen, 3000K

Article nr.: 82415

TECHNICAL DATA

| | |
|-------------------------|-------------|
| IP rating | 20 |
| Power | 24 W |
| Psb | 0,00 W |
| Current mA | 1.000 mA |
| Voltage | 24 V |
| Amount of LED | 350 |
| Temperature range | -20 - 45 |
| LED per meter | 70 |
| Dimension of segments | 100.00 mm |
| Energy efficiency class | EEK-Label_G |
| CRI | ≥ 90 |
| Lifetime L70B50 | 36.000 h |
| Lifetime L90B10 | 13.000 h |





VARDAflex Eco CRI90 - 5 M-Rolle
Flex.LEDStrip, 24V, Innen, 3000K
Article nr.: 82415

TECHNICAL DRAWING

