



Anschlussmöglichkeiten



Elektroausführung



Technische Tabelle

H Bauhöhe mm	L Baulänge mm	T Bautiefe mm	Bautyp	Gewicht (leer) kg	Wasserinhalt l	Oberfläche m ²	Φ 75/65/20°C W	Exponent n	HB mm	HBB mm	VDI 6036 Anford.-klasse erfüllt
831	428	61	BH2083042	10,08	4,08	1,15	546	1,25	82	646	4
	503	61	BH2083050	14,00	4,62	1,31	645	1,25	82	646	4
	603	61	BH2083060	15,95	5,35	1,53	779	1,25	82	646	4
1173	428	61	BH2117042	18,00	5,72	1,60	734	1,26	82	988	4
	503	61	BH2117050	20,76	6,48	1,83	875	1,25	82	988	4
	603	61	BH2117060	24,45	7,52	2,15	1065	1,24	82	988	4
1477	428	61	BH2147042	21,65	7,18	2,01	891	1,23	82	1292	4
	503	61	BH2147050	23,04	8,11	2,29	1062	1,24	82	1292	4
	603	61	BH2147060	24,90	9,42	2,69	1293	1,26	82	1292	4
1743	428	61	BH2174042	21,65	8,58	2,40	1029	1,27	82	1520	4
	503	61	BH2174050	26,13	9,71	2,74	1226	1,27	82	1520	4
	603	61	BH2174060	32,10	11,26	3,22	1593	1,27	82	1520	4